

# ROVELO

# RIDGETRAK

# A/T



LIGHT TRUCK



## ALL TERRAIN

The Rovelo Ridgetrak A/T is designed to deliver superior traction for SUVs, pickups and vans both off and on the road. Approved for severe snow conditions and designed with the 3PMS Mountain/Snowflake symbol. The Ridgetrak A/T provides exceptional handling and on-and-off-road stability while maintaining a comfortable ride. The aggressive open shoulder tread design expels water, snow, slush and mud for optimum traction in all terrain conditions. Extra deep tread sipes at varying angles improves comfort without sacrificing traction.

## 3PMS SEVERE SERVICE DESIGNATION

Approved for severe snow performance.

## AGGRESSIVE OPEN SHOULDER TREAD DESIGN

Maximum performance to expel water, snow, slush and mud for optimum traction in all terrain conditions.

## MULTI-DIRECTIONAL SIPE SYSTEM

Extra deep tread sipes at varying angles improve comfort without sacrificing traction.

## TOUT-TERRAIN

Le Rovelo Ridgetrak A/T est conçu pour assurer une traction maximale aux VUS, aux camionnettes et aux fourgonnettes à la fois sur route et hors route. Approuvé pour rouler dans des conditions de neige difficiles et arborant le symbole Montagne/Flocon de neige, le Ridgetrak A/T offre une tenue de route exceptionnelle et de la stabilité sur route/hors route tout en assurant un confort de roulement. Son épaulement ouvert d'allure agressive chasse l'eau, la neige, la gadoue et la boue pour procurer une traction optimale sur tous types de terrains. Les lamelles très profondes à angles variés améliorent le confort sans sacrifier la traction.

## DÉSIGNATION DE SERVICE DIFFICILE 3PMS :

Approuvé pour performer dans des situations de neige difficiles

## MOTIF D'ÉPAULEMENT OUVERT D'ALLURE AGRESSIVE

Expulsion maximale de l'eau, de la neige, la gadoue et la boue, pour une traction optimale sur tous les types de terrains accidentés.

## RÉSEAU DE LAMELLES MULTIDIRECTIONNEL

Les lamelles très profondes à des angles variés améliorent le confort sans sacrifier la traction.



Part #	Size	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
			32/in.	in.	in.	in.		lbs@psi	lbs@psi
5542625	235/75R15	109S	13	28.9	9.3	6.5	500 A B	2271@50	-
5542630	235/70R16	106S	13	29.0	9.5	7.0	500 A B	2094@44	-
5542624	245/75R16	111S	13	30.5	9.8	7.0	500 A B	2403@44	-
5542631	265/70R16	112T	13	30.6	10.7	8.0	500 A B	2469@44	-
5542626	265/75R16	116S	13	31.7	10.5	7.5	500 A B	2756@44	-
5542638	235/65R17	104S	13	29.1	9.5	7.0	500 A B	1984@44	-
5542639	245/65R17	107S	13	29.5	9.8	7.0	500 A B	2149@44	-
5547982	245/70R17	110T	13	30.6	9.8	7.0	500 A B	2337@44	-
5542637	265/65R17	112S	13	30.6	10.7	8.0	500 A B	2469@44	-
5542632	265/70R17	115S	13	31.7	10.7	8.0	500 A B	2679@44	-
5547983	265/65R18	114T	13	31.5	10.7	8.0	500 A B	2601@44	-
5542643	275/65R18	116T	13	32.1	11.0	8.0	500 A B	2756@44	-
5542650	265/50R20	115T	13	30.5	10.9	8.5	500 A B	2403@50	-
5542641	275/55R20	117T	13	31.9	11.2	8.5	500 A B	2833@50	-
5542642	275/60R20	115T	13	33.0	11.0	8.0	500 A B	2679@44	-
5542628	31x10.50R15LT	109S	16	30.5	10.6	8.5	-	2270@50	-
5542627	LT225/75R16	115/112S	16	29.3	8.8	6.0	-	2680@80	2470@80
5542633	LT235/85R16	120/116R	16	31.7	9.3	6.5	-	3042@80	2778@80
5542623	LT245/75R16	120/116S	16	30.5	9.8	7.0	-	3042@80	2778@80
5542629	LT265/75R16	123/120S	16	31.7	10.5	7.5	-	3415@80	3085@80
5542635	LT285/75R16	126/123R	16	32.8	11.3	8.0	-	3750@80	3415@80
5542644	LT235/80R17	120/117R	16	31.8	9.3	6.5	-	3085@80	2835@80
5542640	LT245/70R17	119/116S	16	30.6	9.8	7.0	-	3000@80	2755@80
5542645	LT245/75R17	121/118S	16	31.5	9.8	7.0	-	3195@80	2910@80
5542634	LT265/70R17	121/118S	16	31.7	10.7	8.0	-	3195@80	2910@80
5542636	LT285/70R17	121/118R	16	32.8	11.5	8.5	-	3195@80	2910@80
5542649	LT265/70R18	124/121R	16	32.6	10.7	8.0	-	3525@80	3195@80
5542646	LT275/65R18	123/120R	16	32.1	11.0	8.0	-	3415@80	3085@80
5542648	LT275/70R18	125/122R	16	33.2	11.0	8.0	-	3640@80	3305@80
5547978	LT265/60R20	121/118R	16	32.5	10.7	8.0	-	3195@80	2910@80
5547984	LT275/55R20	120/117R	16	31.9	11.2	8.5	-	3085@80	2835@80
5547979	LT275/60R20	123/120R	16	33.0	11.0	8.0	-	3415@80	3085@80
5542647	LT275/65R20	126/123R	16	34.1	11.0	8.0	-	3750@80	3415@80
5547980	LT305/55R20	121/118R	16	33.2	12.4	9.5	-	3195@65	2910@65
5547981	LT325/60R20	126/123R	16	35.4	13.0	9.5	-	3750@65	3415@65

\* Black Sidewall