

ROVELO

RIDGETRAK R/T RT01

RUGGED TERRAIN



Meet the Ridgetrak RT tire, expertly engineered for trucks and SUVs. Its purpose-driven design features an optimized tread pattern that guarantees stability across various terrains. A sturdy sidewall with enhanced sidewall biters increases durability and adds to its striking appearance. With its robust visual appeal, this tire commands attention. The RIDGETRAK RT provides ample bite for off-road terrain while maintaining excellent road manners for your daily drive.

RIDE COMFORT

Staggered lateral grooves reduce road noise for the daily commute. While, interlocking tread blocks increase rigidity and eliminates road squirm on the deep RT treads.

DESIGNED WITH PURPOSE

Step-design shoulder lugs look aggressive and provide extra protection to the shoulders and sidewalls..

OFF-ROAD CAPABLE

Aggressive sidewall biters, scalloped alternating shoulders, and stone ejectors guarantee reliable traction.

Voici le pneu Ridgetrak RT, conçu pour les camions et les VUS. Sa conception axée sur la performance présente un dessin de la bande de roulement optimisé qui garantit la stabilité de votre véhicule sur différents terrains. Son flanc robuste favorisant une prise dynamique augmente la durabilité et ajoute à son apparence frappante. Avec son attrait visuel puissant, ce pneu attire l'attention. Le RIDGETRAK RT offre un mordant amplement suffisant pour les terrains hors route tout en conservant d'excellentes qualités routières pour votre conduite quotidienne.

CONFORT DE CONDUITE

Les rainures latérales décalées réduisent le bruit de la route pour les trajets quotidiens. L'emboîtement des pavés de gomme augmente la rigidité et élimine les torsions de la route sur les bandes de roulement profondes du RT.

CONÇU DANS UN BUT PRÉCIS

Les pattes d'épaulement en forme d'escalier ont une allure agressive et offrent une protection supplémentaire aux épaulements et aux flancs.

PERFORMANCE TOUT-TERRAIN

Le flanc robuste favorisant une prise dynamique, les épaulements festonnés alternés et les éjecteurs de pierres garantissent une traction fiable.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)MAX LOAD (2X)		Stud Size
					32/in.	in.	in.		in.	lbs@psi	
1600404K	265/70R17	SL	115T	16	31.65	10.71	8	600/A/B	2679@44		
1600420K	255/70R18	XL	116T	16	32.09	10.24	7	600/A/B	2756@50		
1600403K	265/60R18	XL	114S	16	30.51	10.71	8	600/A/B	2601@50		
1600415K	265/65R18	XL	116T	16	31.54	10.71	8	600/A/B	2756@50		
1600417K	265/70R18	SL	116S	16	32.64	10.71	8	600/A/B	2756@44		
1600407K	275/65R18	XL	116T	16	32.09	10.98	8	600/A/B	2756@50		
1600433K	265/50R20	XL	111T	16	30.47	10.91	8	600/A/B	2403@50		
5042036K	275/55R20	XL	117T	16	31.89	11.18	8	600/A/B	2833@50		
1600421K	275/60R20	XL	116T	16	32.99	10.98	8	600/A/B	2756@50		
1600422K	285/45R22	XL	114Q	16	32.09	11.22	9	600/A/B	2601@50		
1600435K	LT245/70R17	10PR	119/116Q	18	30.55	9.76	7		3000@80	2755@80	15
1600430K	LT245/75R17	10PR	121/118Q	18	31.5	9.76	7		3195@80	2910@80	15
1600405K	LT265/70R17	10PR	123/120Q	18	31.65	10.71	8		3415@80	3085@80	15
1600412K	LT285/70R17	10PR	126/123Q	18	32.76	11.5	8		3750@80	3415@80	15
1600411K	LT265/65R18	10PR	122/119Q	18	31.54	10.71	8		3305@80	3000@80	15
1600429K	LT265/70R18	10PR	124/121Q	18	32.64	10.71	8		3525@80	3195@80	15
1600408K	LT275/65R18	10PR	123/120Q	18	32.09	10.98	8		3415@80	3085@80	15
1600432K	LT275/70R18	10PR	125/122Q	18	33.19	10.98	8		3640@80	3305@80	15
1600436K	LT275/55R20	10PR	120/117Q	18	31.89	11.18	8		3085@80	2835@80	15
1600434K	LT275/60R20	10PR	123/120Q	18	32.99	10.98	8		3415@80	3085@80	15
1600431K	LT275/65R20	10PR	126/123Q	18	34.09	10.98	8		3750@80	3415@80	15
1600428K	LT305/55R20	12PR	125/122Q	18	33.23	12.44	9		3640@80	3305@80	15
1600418K	33X12.50R17LT	10PR	120Q	18	32.52	12.52	10		3085@65		15
1600427K	35X12.50R17LT	10PR	125Q	18	34.53	12.52	10		3640@65		15
1600409K	37X12.50R17LT	8PR	124Q	18	36.54	12.52	10		3525@50		15
1600419K	33X12.50R18LT	12PR	122Q	18	32.52	12.52	10		3305@80		15
1600423K	35X12.50R18LT	12PR	128Q	18	34.53	12.52	10		3970@80		15
1600410K	37X12.50R18LT	10PR	128Q	18	36.54	12.52	10		3970@65		15
1600425K	33X12.50R20LT	12PR	119Q	18	32.52	12.52	10		3000@80		15
1600406K	35X12.50R20LT	12PR	125Q	18	34.53	12.52	10		3640@80		15
1600424K	35X13.50R20LT	12PR	126Q	18	34.53	13.58	10		3750@80		15
1600402K	37X12.50R20LT	10PR	126Q	18	36.54	12.52	10		3750@65		15
1600426K	33X12.50R22LT	12PR	114Q	18	32.52	12.52	10		2600@80		15
1600413K	35X12.50R22LT	12PR	121Q	18	34.53	12.52	10		3195@80		15
1600416K	37X12.50R22LT	12PR	127Q	18	36.54	12.52	10		3860@80		15
1600414K	37X13.50R22LT	12PR	128Q	18	36.54	13.58	10		3970@80		15

* LT tires are pinned for studs