

# ROVELO RIDGETRAK A/T II

LIGHT TRUCK



## ALL TERRAIN

The Ridgetrak A/T II is an updated all-terrain tire for pickup trucks and SUVs. Enhanced 3PMS certified traction, deep tread depth while incorporating a wide tread face provides superior performance for all on and off road driving conditions. Known for consistent reliability, the Ridgetrak A/T II is engineered to be your trusted all-terrain tire providing a quiet comfortable driving experience.

**COMFORT:** Finite Element Analysis simulation software optimizes pitch sequence to reduce resonance effects and aids in a quiet vehicle cabin.

### ENHANCED TRACTION:

3PMS Certified, deep all-terrain tread lugs and altered shoulder tread blocks work together providing trusted traction on all terrains and in all seasons.

**TREADWEAR:** A Wide tread footprint with additional shoulder support promotes even pressure distribution and avoids irregular wear.

## TOUT-TERRAIN

Le pneu Ridgetrak A/T II est un modèle tout-terrain actualisé pour les camionnettes et VUS. Une traction homologuée 3PMS améliorée, une profondeur de sculpture élevée et une large surface de la bande de roulement offrent des performances supérieures pour toutes les conditions de conduite sur et hors route. Connu pour sa constante fiabilité, le pneu Ridgetrak A/T II est conçu pour être votre allié tout-terrain de confiance et procure une expérience de conduite silencieuse et confortable.

**COMFORT :** Le logiciel de simulation d'analyse des éléments finis optimise la séquence du pas pour réduire les effets de résonance et contribue à rendre l'habitacle du véhicule plus silencieux.

**TRACTION ACCRUE :** Les sculptures de la bande de roulement tout-terrain profondes homologuées 3PMS et les pavés d'épaulement modifiés travaillent de concert pour fournir une traction fiable tout-terrain et toutes saisons.

**USURE DE LA BANDE DE ROULEMENT :** Une bande de roulement à empreinte large avec du soutien supplémentaire en matière d'épaulement favorise une répartition de la pression uniforme et permet d'éviter l'usure irrégulière.



Part #	Size	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
				32/in. in.	in.	in.		in.	lbs@psi
4120258V	235/75R15	109S	13	28.9	9.25	6	620 A B	2271@50	-
4120259V	235/70R16	106S	13	29.0	9.45	7	620 A B	2094@44	-
4120260V	245/75R16	111S	13	30.5	9.76	7	620 A B	2403@44	-
4120261V	265/70R16	112T	13	30.6	10.71	8	620 A B	2469@44	-
4120508V	265/75R16	116S	13	31.7	10.51	7	620 A B	2756@44	-
4120509V	235/65R17	104S	13	29.1	9.45	7	620 A B	1984@44	-
4120510V	245/65R17	107S	13	29.5	9.76	7	620 A B	2149@44	-
4120511V	245/70R17	110T	13	30.6	9.76	7	620 A B	2337@44	-
4120512V	255/65R17	110T	13	30.1	10.24	7	620 A B	2337@44	-
4120513V	265/65R17	112S	13	30.6	10.71	8	620 A B	2469@44	-
4120514V	265/70R17	115S	13	31.7	10.71	8	620 A B	2679@44	-
4120515V	265/65R18	114T	13	31.5	10.71	8	620 A B	2601@44	-
4120516V	265/70R18	116T	13	32.6	10.71	8	620 A B	2756@44	-
4120517V	275/65R18	116T	13	32.1	10.98	8	620 A B	2756@44	-
4120518V	265/50R20	111T	13	30.5	10.91	8	620 A B	2403@50	-
4120257V	275/55R20	117T	13	31.8	14.64	8	620 A B	2833@50	-
4120519V	275/60R20	115T	13	33.0	10.98	8	620 A B	2679@44	-
4120526V	285/45R22	114H	13	32.1	11.22	9	620 A B	2601@49	-
4120533V	LT225/75R16	115/112S	16	29.3	8.78	6	-	2680@80	2470@80
4120534V	LT235/85R16	120/116S	16	31.7	9.25	6	-	3042@80	2778@80
4120535V	LT245/75R16	120/116S	16	30.5	9.76	7	-	3042@80	2778@80
4120536V	LT265/75R16	123/120S	16	31.7	10.51	7	-	3415@80	3085@80
4120537V	LT235/80R17	120/117R	16	31.8	9.25	6	-	3085@80	2835@80
4120538V	LT245/70R17	119/116S	16	30.6	9.76	7	-	3000@80	2755@80
4120539V	LT245/75R17	121/118S	16	31.5	9.76	7	-	3195@80	2910@80
4120540V	LT265/70R17	121/118S	16	31.7	10.71	8	-	3415@80	3085@80
4120541V	LT285/70R17	121/118S	16	32.8	11.50	8	-	3750@80	3415@80
TBD	LT315/70R17	121/118S	16	34.4	12.72	9	-	3750@80	3415@80
4120543V	LT265/70R18	124/121S	16	32.6	10.71	8	-	3525@80	3195@80
4120544V	LT275/65R18	123/120R	16	32.1	10.98	8	-	3415@80	3085@80
4120545V	LT275/70R18	125/122R	16	33.2	10.98	8	-	3640@80	3305@80
4120546V	LT265/60R20	121/118R	16	32.5	10.71	8	-	3195@80	2910@80
4120547V	LT275/55R20	120/117R	16	31.9	11.18	8	-	3085@80	2835@80
4120548V	LT275/60R20	123/120R	16	33.0	10.98	8	-	3415@80	3085@80
4120549V	LT275/65R20	126/123R	16	34.1	10.98	8	-	3750@80	3415@80
4120550V	LT285/60R20	125/122R	16	33.5	11.50	8	-	3640@80	3305@80
4120551V	LT305/55R20	121/118R	16	33.2	12.44	9	-	3195@65	2910@65
4120527V	31x10.50R15LT	109S	16	30.5	10.55	8	-	2270@50	-
4120529V	33x12.50R18LT	118S	16	32.5	12.52	10	-	2910@65	-
4120531V	33x12.50R20LT	114S	16	32.5	12.52	10	-	2600@65	-
TBD	35x12.50R17LT	125R	16	34.5	12.52	10	-	3640@80	-
4120530V	35x12.50R18LT	123R	16	34.5	12.52	10	-	3415@65	-
4120532V	35x12.50R20LT	121R	16	34.5	12.52	10	-	3195@65	-