



RIDGETRAK M/T

MUD TERRAIN TIRE

Rovelo Ridgetrak M/T, a bold mud-terrain tire designed to take you further—on and off the road. Its aggressive tread design and wide void spacing provide superior traction and self-cleaning mud evacuation, keeping you in control on unpredictable terrain. Engineered with a tough, reinforced casing, it stands up to harsh conditions while delivering stability. Whether you're navigating trails, rock gardens, or city streets, the Ridgetrak M/T brings strength, confidence, and versatility to every drive.

HEAVY-DUTY BITE

Deep tread depth with staggered lugs enhances off-road capability, while sharp biting edges deliver superior grip on rocky terrain.

SURE-FOOTED CONTROL

Expanded M/T footprint enhances surface engagement, delivering reliable control, supported by aggressive sidewall traction.

TRAIL TOUGHNESS

Our signature 3-ply reinforced casing delivers heavy-duty protection, deflecting sharp debris and absorbing harsh impacts to neutralize the risk of punctures, cuts, and unforeseen trail tears.

Rovelo Ridgetrak M/T es un neumático para terrenos lodosos diseñado para ofrecer un rendimiento confiable dentro y fuera de la carretera. Su agresiva banda de rodadura y amplios surcos proporcionan excelente tracción y una eficaz expulsión del lodo. Con una carcasa reforzada para mayor resistencia y estabilidad, está preparado para afrontar senderos, terrenos rocosos y conducción urbana con confianza y versatilidad.

MORDIDA DE ALTA RESISTENCIA

La banda de rodadura profunda y los tacos escalonados mejoran el desempeño todoterreno, mientras que los bordes agresivos ofrecen mayor agarre en terrenos rocosos.

CONTROL FIRME Y SEGURO

La huella ampliada del neumático M/T mejora el contacto con la superficie y proporciona un control fiable, respaldado por una tracción agresiva en los flancos.

RESISTENCIA EN SENDEROS

Nuestra carcasa reforzada de 3 capas ofrece una protección robusta, desviando residuos afilados y absorbiendo impactos para reducir pinchazos, cortes y daños en el camino.



Item No.	Size	Ply	LI/SR	TD	OD	SW	RW	SINGLE MAX LOAD	DUAL MAX LOAD
				32/in.	in.	in.	in.	lbs@psi	lbs@psi
1608021K	LT235/75R15	6PR	104/101Q	18	28.9	9.3	6.0	1985@50	1820@50
1608020K	LT245/75R16	10PR	120/116Q	18	30.5	9.8	6.5	3042@80	2778@80
1608022K	LT265/75R16	10PR	123/120Q	19	31.7	10.5	7.0	3415@80	3085@80
1608024K	LT285/75R16	10PR	126/123Q	19	32.8	11.3	7.5	3750@80	3415@80
1608018K	LT255/80R17	10PR	123/120Q	19	33.1	10.0	6.5	3415@80	3085@80
2800571K	LT265/70R17	10PR	123/120Q	19	31.7	10.7	7.5	3415@80	3085@80
1608025K	LT285/70R17	10PR	126/123Q	20	32.8	11.5	8.0	3750@80	3415@80
1608034K	LT275/65R18	10PR	123/120Q	20	32.1	11.0	7.5	3415@80	3085@80
1608035K	LT275/70R18	10PR	125/122P	20	33.2	11.0	7.5	3640@80	3305@80
1608023K	LT275/65R20	10PR	126/123Q	19	34.1	11.0	7.5	3750@80	3415@80
1608044K	LT295/65R20	10PR	129/126Q	19	35.1	11.8	8.0	4080@80	3750@80
1608043K	LT295/60R20	10PR	126/123Q	20	33.9	11.8	8.0	3750@80	3415@80
1608019K	31X10.50R15LT	6PR	109Q	19	30.5	10.6	8.0	2270@50	
1608026K	33X12.50R17LT	10PR	120Q	21	32.5	12.5	9.5	3085@65	
1608030K	35X12.50R17LT	10PR	125Q	21	34.5	12.5	9.5	3640@65	
1608027K	33X12.50R18LT	10PR	118Q	21	32.5	12.5	9.5	2910@65	
1608031K	35X12.50R18LT	10PR	123Q	21	34.5	12.5	9.5	3415@65	
1608028K	33X12.50R20LT	12PR	119Q	21	32.5	12.5	9.5	3000@80	
1608032K	35X12.50R20LT	12PR	125Q	21	34.5	12.5	9.5	3640@80	
1608042K	37X12.50R20LT	10PR	126Q	21	36.5	12.5	9.0	3750@65	
1608036K	37X13.50R20LT	12PR	128Q	21	36.5	13.6	9.5	3970@80	
1608029K	33X12.50R22LT	10PR	109Q	21	32.5	12.4	10.0	2270@65	
1608033K	35X12.50R22LT	12PR	121Q	21	34.5	12.5	9.5	3195@80	
1608037K	37X13.50R22LT	12PR	128Q	21	36.5	13.6	9.5	3970@80	
1608040K	33X12.50R24LT	10PR	101Q	21	32.5	12.6	11.0	1820@65	
1608041K	35X12.50R24LT	10PR	117Q	21	34.5	12.4	10.0	2405@65	
1608038K	37X13.50R24LT	12PR	124Q	21	36.5	13.6	10.5	3525@80	
1608017K	35X13.50R26LT	12PR	117Q	21	34.5	13.4	11.5	3305@80	
1608039K	37X13.50R26LT	12PR	117Q	21	36.5	13.4	11.5	2835@80	