

PASSENGER & LIGHT TRUCK TIRES 2026

+ ROVELOTIREUSA.COM

ROVELO

ABOUT ROVELO

Developed in North America for North American roads -- Rovelo is a leader in value, armed with a wide range of popular sizes and applications for cars, trucks, crossovers and SUV tires. Focused on manufacturing high-quality tires that bring great value to everyday drivers, Rovelo delivers affordable performance you can count on.

Determined to manufacture top quality tires for a wide range of vehicles, Rovelo engineers use a methodical approach when it comes to research, development, and testing, which maximizes the effectiveness of Rovelo's advanced manufacturing process. Rovelo tires offer a specialized line up of products designed to meet and exceed expectations at an unbeatable price.

ACERCA DE ROVELO

Desarrollado en Norteamérica para carreteras norteamericanas: Rovelo es un líder en valor, armado con una amplia gama de tamaños y aplicaciones populares para automóviles, camionetas, crossovers y neumáticos SUV. Centrado en la fabricación de neumáticos de alta calidad que aportan un gran valor a los conductores cotidianos, Rovelo ofrece un rendimiento asequible en el que puede confiar.

Decididos a fabricar neumáticos de alta calidad para una amplia gama de vehículos, los ingenieros de Rovelo utilizan un enfoque metódico cuando se trata de investigación, desarrollo y pruebas, lo que maximiza la eficacia del avanzado proceso de fabricación de Rovelo. Los neumáticos Rovelo ofrecen una línea especializada de productos diseñados para cumplir y superar las expectativas a un precio inmejorable.



TABLE OF CONTENTS | PASSENGER & LIGHT TRUCK TIRE 2025



04 INSTINCT AS01
All-Season Touring



06 INSTINCT UHP AS HP01
Ultra-High Performance All-Season Tire



08 INSTINCT AW
All-Weather Tire



10 INSTINCT SUV
All-Season SUV Tire



12 RIDGETRAK H/T HT02
Highway Terrain Tire


14 RIDGETRAK A/T II
Light Truck, All-Terrain Tire


16 RIDGETRAK R/T RT01
Rugged Terrain Tire



18 RIDGETRAK LMD HT02



20 ARCTIC VISION RW01
Studdable Winter Tire



22 ARCTIC VISION LT
Studdable Winter Tire

ROVELO

INSTINCT AS01

ALL-SEASON TOURING TIRE

The Instinct AS01 all-season touring tire lets you and your vehicle become one with the road. Four wide circumferential tire grooves help channel water away from the tire to provide excellent wet and dry traction. The center rib provides directional stability with biting edges for added traction and the wide shoulder lugs promote even wear and fantastic cornering.

CENTER RIB WITH ANGLED SIPES

Provides confident stability with enhanced traction.

BALANCED VARIABLE PITCH SHOULDER DESIGN

Promotes a quiet and comfortable ride.

FULL SIPED INNER TREAD BLOCKS

Efficient water evacuation design promotes enhanced wet performance.

El neumático touring para todas las temporadas Instinct AS01 le permite a usted y a su vehículo convertirse en uno con el camino. Cuatro surcos de neumático circunferenciales amplios ayudan a canalizar el agua para alejarla del neumático y proporcionar tracción húmeda y seca excelente. La costilla central proporciona estabilidad direccional con bordes marcados para tracción agregada, y los huecos de los hombros promueven el desgaste uniforme y un fantástico giro.

COSTILLA CENTRAL CON MICROSURCOS EN ÁNGULO

Proporciona estabilidad confiable con tracción mejorada.

DISEÑO DE HOMBRO CON PASO VARIABLE BALANCEADO

Promueve una conducción silenciosa y cómoda.

BLOQUES DE BANDA DE RODAMIENTO INTERNO CON MICROSURCOS COMPLETOS

El diseño para evacuación eficiente de agua promueve un desempeño húmedo mejorado.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.	in.		lbs@psi
9630963	175/65R14	XL	86T	10	23.0	7.0	5.0	420 A A	1168@50
9630958	175/70R14		84T	10	23.7	7.0	5.0	420 A A	1102@44
9630947	185/65R14		86H	10	23.5	7.4	5.5	420 A A	1168@44
9630955	195/70R14		91T	10	24.8	7.9	6.0	420 A A	1356@44
9630978	175/55R15		77H	10	22.6	7.2	5.5	420 A A	908@44
9630971	175/65R15		84H	10	24.0	7.0	5.0	420 A A	1102@44
9630957	185/55R15		82V	10	23.0	7.6	6.0	420 A A	1047@44
9630945	185/60R15	XL	88H	10	23.7	7.4	5.5	420 A A	1235@50
9630939	185/65R15	XL	92H	10	24.4	7.4	5.5	420 A A	1389@50
9630941	195/60R15		88H	10	24.2	7.9	6.0	420 A A	1235@44
9630932	195/65R15		91H	10	25.0	7.9	6.0	420 A A	1356@44
9630964	205/60R15		95H	10	24.7	8.2	6.0	420 A A	1521@50
9630942	205/65R15		94H	10	25.5	8.2	6.0	420 A A	1477@44
9630953	205/70R15		96T	10	26.3	8.2	6.0	420 A A	1565@44
9630946	215/70R15		98T	10	26.9	8.7	6.5	420 A A	1653@44
9630972	195/50R16		84V	10	23.7	7.9	6.0	420 A A	1102@44
9630970	195/55R16		87H	10	24.4	7.9	6.0	420 A A	1201@44
9630966	205/50R16		87H	10	24.1	8.4	6.5	420 A A	1201@44
9630929	205/55R16		91H	10	24.9	8.4	6.5	420 A A	1356@44
9630938	205/60R16		92H	10	25.7	8.2	6.0	420 A A	1389@44
9630937	205/65R16		95H	10	26.5	8.2	6.0	420 A A	1521@44
9630940	215/55R16	XL	97H	10	25.3	8.9	7.0	420 A A	1609@50
9630931	215/60R16		95H	10	26.1	8.7	6.5	420 A A	1521@44
9630944	215/65R16		98T	10	27.0	8.7	6.5	420 A A	1653@44
9630935	225/60R16		98H	10	26.6	9.0	6.5	420 A A	1653@44
9630954	225/65R16		100H	10	27.5	9.0	6.5	420 A A	1764@44
9630977	235/60R16		100V	10	27.1	9.4	7.0	420 A A	1764@44
9630965	235/65R16		103T	10	28.0	9.4	7.0	420 A A	1929@44
9630959	205/50R17		89V	10	25.1	8.4	6.5	420 A A	1728@44
9630967	215/45R17		87W	10	24.6	8.4	7.0	420 A A	1201@44
9630960	215/50R17		91V	10	25.5	8.9	7.0	420 A A	1356@44
9630930	215/55R17		94V	10	26.3	8.9	7.0	420 A A	1477@44
9630950	215/60R17		96T	10	27.2	8.7	6.5	420 A A	1565@44
9630952	215/65R17		99T	10	28.0	8.7	6.5	420 A A	1709@44
9630949	225/45R17		91V	10	25.0	8.9	7.5	420 A A	1356@44
9630934	225/50R17		94V	10	25.9	9.2	7.0	420 A A	1477@44
9630936	225/55R17		97V	10	26.8	9.2	7.0	420 A A	1609@44
9630943	225/60R17		99H	10	27.6	9.0	6.5	420 A A	1709@44
9630933	225/65R17		102T	10	28.5	9.0	6.5	420 A A	1874@44
9630969	235/45R17	XL	97W	10	25.4	9.3	8.0	420 A A	1609@50
9630962	235/55R17		99V	10	27.2	9.6	7.5	420 A A	1709@44
9630976	225/40R18	XL	92W	10	25.1	9.1	8.0	420 A A	1389@50
9630961	225/50R18		95H	10	26.9	9.2	7.0	420 A A	1521@44
9630968	235/45R18		94V	10	26.3	9.3	8.0	420 A A	1477@44
9630956	235/50R18		97V	10	27.3	9.6	7.5	420 A A	1609@44
9630948	235/55R18		100V	10	28.1	9.6	7.5	420 A A	1764@44
9630951	235/60R18		103H	10	29.1	9.4	7.0	420 A A	1929@44
9630975	245/40R18	XL	97W	10	25.7	9.8	8.5	420 A A	1609@50
9630974	245/45R18	XL	100W	10	26.7	9.6	8.0	420 A A	1764@50
9630973	235/55R19	XL	105V	10	29.2	9.6	7.5	420 A A	2039@50

ROVELO

INSTINCT UHP AS HP01

ULTRA-HIGH PERFORMANCE ALL-SEASON TIRE

Engineered with advanced materials and innovative design, the Rovelo Instinct UHP AS HP01 tire offers outstanding wear resistance, enhanced traction, stability, and noise reduction. Experience high-performance driving comfort and reliability, whether commuting daily or embarking on long road trips.

PREMIUM STRUCTURAL DESIGN

High-strength belt ply package ensures tread rigidity and high-speed stability.

ENHANCED CONTOUR DESIGN

Optimized sidewall contour reduces road impact and vibrations providing unmatched comfort for a UHP AS tire.

QUIET PERFORMANCE

Innovative asymmetric tread pattern with strategically arranged tread blocks minimize road noise while providing excellent cornering grip.

Ideado con materiales avanzados y un diseño innovador, el neumático Rovelo Instinct UHP AS HP01 ofrece resistencia excepcional al desgaste, tracción mejorada, estabilidad y reducción de ruido. Experimente la comodidad de conducción de alto desempeño y la confiabilidad, ya sea durante su traslado urbano cotidiano o al embarcarse en viajes largos en automóvil.

DISEÑO ESTRUCTURAL PREMIUM

El paquete de capas de banda de alta resistencia asegura la rigidez de la banda de rodamiento y la estabilidad a alta velocidad.

DISEÑO DE MOLDEADO MEJORADO

El moldeado optimizado de la pared lateral reduce el impacto y las vibraciones del camino, ofreciendo comodidad incomparable para un neumático UHP AS.

DESEMPEÑO SILENCIOSO

El patrón asimétrico de la banda de rodamiento con bloques de banda de rodamiento colocados estratégicamente minimiza el ruido del camino mientras ofrece un excelente agarre durante los giros.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.	in.		lbs@psi
1600957K	205/45R16	XL	87W	10	23.0	8.1	7.0	600 A A	1201@50
1600959K	205/50R16		87W	10	23.9	8.4	6.5	600 A A	1201@44
1600961K	205/55R16		91W	10	24.8	8.4	6.5	600 A A	1356@44
1600965K	215/55R16	XL	97W	10	25.1	8.9	7.0	600 A A	1609@50
1600958K	205/45R17	XL	88W	10	24.1	8.1	7.0	600 A A	1235@50
1600960K	205/50R17	XL	93W	10	25.0	8.4	6.5	600 A A	1433@50
1600962K	215/45R17	XL	91W	10	24.5	8.4	7.0	600 A A	1356@50
1600964K	215/50R17		91V	10	25.4	8.9	7.0	600 A A	1356@44
1600966K	215/55R17	XL	98W	10	26.1	8.9	7.0	600 A A	1653@50
1600995K	225/45R17		91V	10	25.0	8.9	7.5	600 A A	1356@44
1601027K	225/50R17	XL	98V	10	25.9	9.2	7.0	600 A A	1653@50
1601029K	225/55R17	XL	101W	10	26.8	9.2	7.0	600 A A	1819@50
1601035K	235/45R17	XL	97W	10	25.4	9.3	8.0	600 A A	1609@50
1601026K	235/50R17	XL	100W	10	26.3	9.6	7.5	600 A A	1764@50
1600905K	235/55R17	XL	103W	10	27.2	9.6	7.5	600 A A	1929@50
1601044K	245/40R17	XL	95V	10	24.7	9.8	8.5	600 A A	1521@50
1601048K	245/45R17	XL	99W	10	25.7	9.6	8.0	600 A A	1709@50
1600963K	215/45R18	XL	93W	10	25.5	8.4	7.0	600 A A	1433@50
1600967K	225/40R18	XL	92W	10	24.9	9.1	8.0	600 A A	1389@50
1600996K	225/45R18	XL	95W	10	25.9	8.9	7.5	600 A A	1521@50
1601028K	225/50R18	XL	99W	10	26.9	9.2	7.0	600 A A	1709@50
1601030K	225/55R18	XL	102W	10	27.8	9.2	7.0	600 A A	1874@50
1601033K	235/40R18	XL	95W	10	25.4	9.5	8.5	600 A A	1521@50
1601036K	235/45R18	XL	98W	10	26.3	9.3	8.0	600 A A	1653@50
1601037K	235/50R18		97W	10	27.3	9.6	7.5	600 A A	1609@44
1601039K	235/55R18	XL	104W	10	28.1	9.6	7.5	600 A A	1984@50
1601045K	245/40R18	XL	97W	10	25.7	9.8	8.5	600 A A	1609@50
1601049K	245/45R18	XL	100W	10	26.7	9.6	8.0	600 A A	1764@50
1601054K	245/55R18	XL	107W	10	28.6	10.0	7.5	600 A A	2149@50
1601055K	255/35R18		90W	10	25.0	10.2	9.0	600 A A	1323@44
1600968K	225/40R19	XL	93W	10	25.9	9.1	8.0	600 A A	1433@50
1601025K	225/45R19		92W	10	27.0	8.9	7.5	600 A A	1389@44
1601031K	225/55R19	XL	103W	10	28.8	9.2	7.0	600 A A	1929@50
1601032K	235/35R19	XL	91W	10	25.5	9.5	8.5	600 A A	1356@50
1601034K	235/40R19		92W	10	26.4	9.5	8.5	600 A A	1389@44
1601038K	235/50R19	XL	103W	10	28.3	9.6	7.5	600 A A	1929@50
1601040K	235/55R19	XL	105W	10	29.2	9.6	7.5	600 A A	2039@50
1601042K	245/35R19	XL	93W	10	25.8	9.8	8.5	600 A A	1433@50
1601046K	245/40R19	XL	98W	10	26.7	9.8	8.5	600 A A	1653@50
1601050K	245/45R19	XL	102W	10	27.7	9.6	8.0	600 A A	1874@50
1601052K	245/50R19		101W	10	28.7	10.0	7.5	600 A A	1819@44
1601056K	255/35R19	XL	96W	10	26.0	10.2	9.0	600 A A	1565@50
1601057K	255/40R19	XL	100W	10	27.0	10.2	9.0	600 A A	1764@50
1601059K	255/45R19	XL	104W	10	28.1	10.0	8.5	600 A A	1984@50
1601062K	275/40R19		101W	10	27.7	10.9	8.5	600 A A	1819@44
1601041K	235/55R20		102W	10	30.2	9.6	7.5	600 A A	1874@44
1601043K	245/35R20	XL	95W	10	26.8	9.8	8.5	600 A A	1521@50
1601047K	245/40R20	XL	99Y	10	27.7	9.8	8.5	600 A A	1709@50
1601051K	245/45R20	XL	103Y	10	28.7	9.6	8.0	600 A A	1929@50
1601053K	245/50R20	XL	105W	10	29.7	10.0	7.5	600 A A	2039@50
1601058K	255/40R20	XL	101Y	10	28.0	10.2	9.0	600 A A	1819@50
1601060K	255/45R20	XL	105Y	10	29.1	10.0	8.5	600 A A	2039@50
1601061K	275/35R20	XL	102Y	10	27.6	10.9	9.5	600 A A	1874@50
1601063K	275/40R20	XL	106Y	10	28.7	10.9	9.5	600 A A	2094@50

ROVELO

2 YEAR ROAD HAZARD REPLACEMENT PROGRAM

LIMITED TREADLIFE PROTECTION 60K MILE MILEAGE WARRANTY LIMITED TREADLIFE PROTECTION

INSTINCT AW

ALL-WEATHER TIRE

Designed for year-round confidence, Rovelo Instinct AW combines the agility of a high-performance all-season with the traction of a winter tire. Its asymmetric tread pattern offers superior grip and handling on wet, snowy, and dry roads, while the advanced rubber compound stays flexible even in sub-zero temperatures. With 3-Peak Mountain Snowflake (3PMSF) certification, it's ready for winter while delivering a quiet, comfortable ride in every season.

YEAR-ROUND CONVENIENCE

No seasonal tire change required, offering a cost-effective solution. Designed to handle both warm and cold conditions, with 3-Peak Mountain Snowflake certification.

CONSISTENT PERFORMANCE

The asymmetrical tread works in three zones: inner tread for water evacuation, outer tread for cornering and dry grip, and a center rib for stability and quick steering.

Diseñado para todo el año, Rovelo Instinct AW combina la agilidad de un neumático de alto rendimiento con la tracción de invierno. Su dibujo asimétrico brinda agarre y control en mojado, nieve y seco, mientras que el compuesto avanzado permanece flexible en frío extremo. Con certificación 3PMSF, ofrece un viaje silencioso y cómodo en cualquier estación.

COMODIDAD TODO EL AÑO

No requiere cambio de neumáticos según la temporada, lo que ofrece una solución rentable. Diseñado para soportar condiciones tanto cálidas como frías, con certificación 3-Peak Mountain Snowflake.

RENDIMIENTO CONSTANTE

La banda de rodadura asimétrica funciona en tres zonas: banda de rodadura interior para la evacuación del agua, banda de rodadura exterior para tomar curvas y tener agarre en seco, y una nervadura central para estabilidad y dirección rápida.



Part #	Size	Ply	L.R.	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.	in.		lbs@psi
1603910K	185/65R15	88H		11	24.4	7.4	5.5	500 A A	1235@44
1603911K	195/65R15	91H		11	25.0	7.9	6.0	500 A A	1356@44
1603912K	205/55R16	91V		11	24.9	8.4	6.5	500 A A	1356@44
1603913K	205/60R16	96V	XL	11	25.7	8.2	6.0	500 A A	1565@50
1603914K	205/65R16	95H		11	26.5	8.2	6.0	500 A A	1521@44
1603915K	215/55R16	93V		11	25.3	8.9	7.0	500 A A	1433@44
1603916K	215/60R16	99H	XL	11	26.1	8.7	6.5	500 A A	1709@50
1603917K	215/65R16	102H	XL	11	27.0	8.7	6.5	500 A A	1874@50
1603918K	235/70R16	106H		11	29.0	9.4	7.0	500 A A	2094@44
1603919K	205/50R17	93V	XL	11	25.1	8.4	6.5	500 A A	1433@50
1603920K	215/45R17	91W	XL	11	24.6	8.4	7.0	500 A A	1356@50
1603921K	215/50R17	95W	XL	11	25.5	8.9	7.0	500 A A	1521@50
1603922K	215/55R17	98V	XL	11	26.3	8.9	7.0	500 A A	1653@50
1603923K	215/60R17	100H	XL	11	27.2	8.7	6.5	500 A A	1764@50
1603924K	215/65R17	103H	XL	11	28.0	8.7	6.5	500 A A	1929@50
1603925K	225/45R17	94V	XL	11	25.0	8.9	7.5	500 A A	1477@50
1603926K	225/50R17	98V	XL	11	25.9	9.2	7.0	500 A A	1653@50
1603927K	225/55R17	101V	XL	11	26.8	9.2	7.0	500 A A	1819@50
1603928K	225/60R17	103H	XL	11	27.6	9.0	6.5	500 A A	1929@50
1603929K	225/65R17	102H		11	28.5	9.0	6.5	500 A A	1874@44
1603930K	235/55R17	103V	XL	11	27.2	9.6	7.5	500 A A	1929@50
1603931K	235/65R17	108H	XL	11	29.1	9.4	7.0	500 A A	2205@50
1603932K	225/40R18	92V	XL	11	25.1	9.1	8.0	500 A A	1389@50
1603933K	225/45R18	95V	XL	11	25.9	8.9	7.5	500 A A	1521@50
1603934K	225/50R18	99V	XL	11	26.9	9.2	7.0	500 A A	1709@50
1603935K	225/55R18	102V	XL	11	27.8	9.2	7.0	500 A A	1874@50
1603936K	225/60R18	104H	XL	11	28.6	9.0	6.5	500 A A	1984@50
1603937K	235/40R18	95V	XL	11	25.4	9.5	8.5	500 A A	1521@50
1603938K	235/45R18	98W	XL	11	26.3	9.3	8.0	500 A A	1653@50
1603939K	235/50R18	101V	XL	11	27.3	9.6	7.5	500 A A	1819@50
1603940K	235/55R18	104V	XL	11	28.1	9.6	7.5	500 A A	1984@50
1605392K	235/60R18	107V	XL	11	29.1	9.4	7.0	500 A A	2149@50
1603942K	235/65R18	110H	XL	11	30.0	9.4	7.0	500 A A	2337@50
1603943K	245/40R18	97W	XL	11	25.7	9.8	8.5	500 A A	1609@50
1603944K	245/60R18	109H	XL	11	29.6	9.8	7.0	500 A A	2271@50
1603945K	225/55R19	103V	XL	11	28.8	9.2	7.0	500 A A	1929@50
1603946K	235/40R19	96V	XL	11	26.4	9.5	8.5	500 A A	1565@50
1603947K	235/50R19	103W	XL	11	28.3	9.6	7.5	500 A A	1929@50
1603948K	235/55R19	105V	XL	11	29.2	9.6	7.5	500 A A	2039@50
1603949K	245/45R19	102V	XL	11	27.7	9.6	8.0	500 A A	1874@50
1603950K	255/35R19	96V	XL	11	26.0	10.2	9.0	500 A A	1565@50
1603951K	255/40R19	100V	XL	11	27.0	10.2	9.0	500 A A	1764@50
1603952K	235/55R20	105V	XL	11	30.2	9.6	7.5	500 A A	2039@50
1603953K	245/45R20	103V	XL	11	28.7	9.6	8.0	500 A A	1929@50
1603954K	245/50R20	105V	XL	11	29.7	10.0	7.5	500 A A	2039@50
1603955K	255/45R20	105V	XL	11	29.1	10.0	8.5	500 A A	2039@50
1603956K	265/50R20	111V	XL	11	30.5	10.9	8.5	500 A A	2403@50
1603957K	235/65R16C	121/119R	E	13	28.0	9.4	7.0		3197@83

ROVELO

INSTINCT SUV

ALL-SEASON SUV TIRE

The SUV/CUV has become the vehicle of choice in North America thanks to their ability to carry passengers and cargo for a go-anywhere, do-anything attitude. The Rovelo Instinct SUV tire was engineered to compliment the SUV segment providing excellent handling and traction along with the heavier loads of SUVs.

HANDLING

Wide tread surface plus a unique shoulder profile design delivers more even contact pressure increasing handling performance.

COMFORT

Proprietary rubber under tread compound enhances ride comfort, while reducing road vibration and road noise.

TRACTION

4 wide circumferential and lateral grooves channel moisture for improved wet braking and handling.

El vehículo utilitario deportivo (SUV)/VUC se ha vuelto el vehículo de elección en Norteamérica gracias a su capacidad de transportar pasajeros y carga a cualquier lugar, con actitud todoterreno. El neumático Rovelo Instinct SUV fue diseñado para complementar al segmento, ofreciendo excelente manejo y tracción con las cargas más pesadas de los SUV.

MANEJO

La superficie de banda de rodamiento amplia más un diseño de perfil único de hombro proporcionan presión de contacto más uniforme, incrementando el desempeño de manejo.

COMODIDAD

El compuesto patentado de caucho bajo la banda de rodamiento mejora la comodidad de la conducción, mientras reduce la vibración y el ruido del camino.

TRACCIÓN

Cuatro surcos circunferenciales amplios trabajan con los surcos laterales que canalizan efectivamente la humedad para alejarla del neumático.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.	in.		lbs@psi
4120098K	215/65R16		103T	10	27.0	8.7	6.5	700 A A	1653@44
4120096K	215/70R16		100H	10	27.9	8.7	6.5	700 A A	1764@44
1602499K	225/70R16		103T	10	28.4	8.9	6.5	700 A A	1929@44
4120099K	235/60R16		100H	10	27.1	9.4	7.0	700 A A	1764@44
4120118K	245/70R16		107T	10	29.5	9.8	7.0	700 A A	2149@44
4120106K	255/70R16		111H	10	30.1	10.2	7.5	700 A A	2403@44
4120105K	265/70R16		112H	10	30.6	10.7	8.0	700 A A	2469@44
4120100K	215/60R17		96H	10	27.2	8.7	6.5	700 A A	1565@44
4120120K	225/55R17		97V	10	26.8	9.2	7.0	700 A A	1609@44
4120108K	225/60R17		99H	10	27.6	9.0	6.5	700 A A	1709@44
4120109K	225/65R17		102H	10	28.5	9.0	6.5	700 A A	1874@44
4120128K	235/55R17		99V	10	27.2	9.6	7.5	700 A A	1709@44
4120097K	235/60R17		102H	10	28.1	9.4	7.0	700 A A	1874@44
4120107K	235/65R17		104H	10	29.1	9.4	7.0	700 A A	1984@44
4120117K	245/65R17		107H	10	29.5	9.8	7.0	700 A A	2149@44
4120115K	255/60R17		106H	10	29.1	10.2	7.5	700 A A	2094@44
4120094K	265/65R17		112H	10	30.6	10.7	8.0	700 A A	2469@44
4120104K	215/55R18		95H	10	27.3	8.9	7.0	700 A A	1521@44
4120091K	225/55R18		98V	10	27.8	9.2	7.0	700 A A	1653@44
4120114K	225/60R18		100H	10	28.6	9.0	6.5	700 A A	1764@44
4120119K	235/50R18		97V	10	27.3	9.6	7.5	700 A A	1609@44
4120089K	235/55R18		100V	10	28.1	9.6	7.5	700 A A	1764@44
4120116K	235/60R18	XL	107V	10	29.1	9.4	7.0	700 A A	2149@50
4120085K	235/65R18		106H	10	30.0	9.4	7.0	700 A A	2094@44
4120113K	245/60R18		105H	10	29.6	9.8	7.0	700 A A	2039@44
4120127K	255/55R18	XL	109V	10	29.0	10.4	8.0	700 A A	2271@50
1607756K	255/60R18	XL	112V	10	30.0	10.2	7.5	700 A A	2469@50
4120090K	255/65R18		111T	10	31.1	10.2	7.5	700 A A	2403@44
4120112K	265/60R18		110H	10	30.5	10.7	8.0	700 A A	2337@44
4120121K	225/55R19		99V	10	28.8	9.2	7.0	700 A A	1709@44
4120095K	235/45R19		95V	10	27.4	9.3	8.0	700 A A	1521@44
4120092K	235/50R19	XL	103V	10	28.3	9.6	7.5	700 A A	1929@50
4120132K	235/55R19	XL	105V	10	29.2	9.6	7.5	700 A A	2039@50
4120129K	245/55R19		103V	10	29.6	10.0	7.5	700 A A	1929@44
4120088K	255/50R19	XL	107V	10	29.1	10.4	8.0	700 A A	2149@50
4120123K	255/55R19	XL	111V	10	30.0	10.4	8.0	700 A A	2403@50
4120111K	255/60R19		109H	10	31.1	10.2	7.5	700 A A	2271@44
4120086K	265/50R19	XL	110V	10	29.5	10.9	8.5	700 A A	2337@50
4120130K	235/55R20	XL	105V	10	30.2	9.6	7.5	700 A A	2039@50
4120133K	245/50R20		102V	10	29.7	10.0	7.5	700 A A	1874@44
4120110K	245/60R20		107H	10	31.6	9.8	7.0	700 A A	2149@44
4120084K	255/50R20	XL	109V	10	30.1	10.4	8.0	700 A A	2271@50
4120125K	255/55R20	XL	110V	10	31.0	10.4	8.0	700 A A	2337@50
4120122K	265/50R20		107H	10	30.5	10.9	8.5	700 A A	2149@44
4120124K	275/40R20	XL	106W	10	28.7	10.9	9.5	700 A A	2094@50
4120101K	265/40R21	XL	105W	10	29.3	10.7	9.5	700 A A	2039@50
4120102K	275/40R21	XL	107W	10	29.6	10.9	9.5	700 A A	2149@50
4120131K	275/45R21	XL	110W	10	30.7	10.7	9.0	700 A A	2337@50
4120126K	285/40R21	XL	109W	10	30.0	11.4	10.0	700 A A	2271@50
4120103K	295/35R21	XL	107W	10	29.1	11.9	10.5	700 A A	2149@50
4120093K	315/40R21	XL	115W	10	30.9	12.6	11.0	700 A A	2679@50

ROVELO

RIDGETRAK H/T HT02

HIGHWAY TERRAIN TIRE

The Ridgetrak H/T HT02 is an excellent all-season highway terrain tire for light trucks, SUVs and crossovers, providing excellent traction, a quiet ride, and consistent handling for a comfortable and enjoyable drive anytime.

EXCELLENT TRACTION

Special polymer compound with zig-zag siping design enhances wet traction with confident control for all weather and road conditions.

RIDE COMFORT

Modern noise simulation technology optimizes tread design for a quiet ride.

CONSISTENT HANDLING

Shoulder tie-bar design in the lateral grooves increase stability and promotes even wear.

El Ridgetrak H/T HT02 es un excelente neumático de terreno de carretera para todas las temporadas para camionetas ligeras, SUV y crossovers, proporcionando tracción, conducción silenciosa y un manejo consistente para una conducción cómoda y agradable cada vez.

TRACCIÓN EXCELENTE

El compuesto de polímero especial con diseño de microsurcos en zig-zag mejora la tracción húmeda con control confiable para todo tipo de clima y de condiciones de camino.

COMODIDAD DE VIAJE

La tecnología de simulación de ruido moderna optimiza el diseño de la banda de rodamiento para una conducción silenciosa.

MANEJO UNIFORME

El diseño de barra de acoplamiento en los surcos laterales del hombro incrementa la estabilidad y promueve el desgaste regular.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
				32/in.	in.	in.	in.		lbs@psi	lbs@psi
4120328K	235/75R15		105T	11	28.9	9.3	6.5	700 A A	2039@44	
4120323K	235/70R16		106T	11	29.0	9.4	7.0	700 A A	2094@44	
4120325K	245/70R16		107T	11	29.5	9.8	7.0	700 A A	2149@44	
4120322K	245/75R16		111T	11	30.5	9.8	7.0	700 A A	2403@44	
4120330K	255/70R16		111T	11	30.1	10.2	7.5	700 A A	2403@44	
4120317K	265/70R16		112T	11	30.6	10.7	8.0	700 A A	2469@44	
4120324K	265/75R16		116T	11	31.7	10.5	7.5	700 A A	2756@44	
4120326K	235/75R17		109T	11	30.9	9.3	6.5	700 A A	2271@44	
4120327K	245/65R17		107T	11	29.5	9.8	7.0	700 A A	2149@44	
4120318K	245/70R17		110T	11	30.6	9.8	7.0	700 A A	2337@44	
1605181K	255/70R17		112T	11	31.1	10.2	7.5	700 A A	2468@44	
4120320K	265/65R17		112S	11	30.6	10.7	8.0	700 A A	2469@44	
4120301K	265/70R17		115T	11	31.7	10.7	8.0	700 A A	2679@44	
4120306K	255/70R18		113T	11	32.1	10.2	7.5	700 A A	2535@44	
4120307K	265/60R18		110H	11	30.5	10.7	8.0	700 A A	2337@44	
4120313K	265/65R18		114T	11	31.5	10.7	8.0	700 A A	2601@44	
4120311K	265/70R18		116T	11	32.6	10.7	8.0	700 A A	2756@44	
4120304K	275/65R18		116T	11	32.1	11.0	8.0	700 A A	2756@44	
4120310K	265/50R20		107V	11	30.5	10.9	8.5	700 A A	2149@44	
1605382K	275/50R22	SL	111H	11	32.9	11.2	8.5	700 A A	2403@44	
4120302K	275/55R20	XL	117T	11	31.9	11.2	8.5	700 A A	2833@50	
4120303K	275/60R20		115T	11	33.0	11.0	8.0	700 A A	2679@44	
4120319K	285/45R22	XL	114H	11	32.1	11.2	9.5	700 A A	2601@50	
4120316K	LT215/85R16	10PR	115/112R	14	30.4	8.5	6.0		2680@80	2470@80
4120315K	LT225/75R16	10PR	115/112R	14	29.3	8.8	6.0		2680@80	2470@80
4120334K	LT235/85R16	10PR	120/116R	14	31.7	9.3	6.5		3042@80	2778@80
4120332K	LT245/75R16	10PR	120/116R	14	30.5	9.8	7.0		3042@80	2778@80
4120333K	LT265/75R16	10PR	123/120R	14	31.7	10.5	7.5		3415@80	3085@80
4120331K	LT235/80R17	10PR	120/117R	14	31.8	9.3	6.5		3085@80	2835@80
4120321K	LT245/70R17	10PR	119/116S	14	30.6	9.8	7.0		3000@80	2755@80
4120329K	LT245/75R17	10PR	121/118S	14	31.5	9.8	7.0		3195@80	2910@80
4120314K	LT265/70R17	10PR	123/120S	14	31.7	10.7	8.0		3415@80	3085@80
4120309K	LT265/70R18	10PR	124/121S	14	32.6	10.7	8.0		3525@80	3195@80
4120308K	LT275/65R18	10PR	123/120S	14	32.1	11.0	8.0		3415@80	3085@80
4120305K	LT275/70R18	10PR	125/122S	14	33.2	11.0	8.0		3640@80	3305@80
4120312K	LT275/65R20	10PR	126/123S	14	34.1	11.0	8.0		3750@80	3415@80

ROVELO

RIDGETRAK A/T II

LIGHT TRUCK, ALL-TERRAIN TIRE

The Ridgetrak A/T II is an all-terrain tire for pickup trucks and SUVs. Enhanced 3PMS certified traction, deep tread depth while incorporating a wide tread face provides superior performance for all on and off road driving conditions. Known for consistent reliability, the Ridgetrak A/T II is engineered to be your trusted all-terrain tire.

COMFORT

Finite Element Analysis simulation software optimizes pitch sequence to reduce resonance effects and aids in a quiet vehicle cabin.

ENHANCED TRACTION

Deep all-terrain tread lugs and altered shoulder tread blocks work together providing traction on all terrains and in all seasons.

TREADWEAR

A wide tread footprint with additional shoulder support promotes even pressure distribution and avoids irregular wear.

El Ridgetrak A/T II es un neumático todoterreno actualizado para camionetas pickup y SUV. Tracción certificada 3PMS, mayor profundidad de banda de rodamiento y una superficie amplia garantizan desempeño superior en todas las condiciones de conducción dentro y fuera del camino. Reconocido por su confiabilidad, el Ridgetrak A/T II está diseñado para ser su neumático todoterreno de confianza.

COMODIDAD

El software de simulación de elemento finito optimiza la secuencia de paso para reducir los efectos de resonancia y ayuda a tener una cabina de vehículo silenciosa.

TRACCIÓN MEJORADA

Los tacos profundos y los bloques de hombro modificados ofrecen tracción en todo terreno y temporada.

DESGASTE DE LA BANDA DE RODAMIENTO

Una huella amplia y soporte en los hombros aseguran presión uniforme y evitan desgaste irregular.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
				32/in.	in.	in.	in.		lbs@psi	lbs@psi
4120258K	235/75R15	XL	109S	13	28.9	9.3	6.0	620 A B	2271@50	
4120259K	235/70R16		106S	13	29	9.5	7.0	620 A B	2094@44	
4120260K	245/75R16		111S	13	30.5	9.8	7.0	620 A B	2403@44	
4120261K	265/70R16		112T	13	30.6	10.7	8.0	620 A B	2469@44	
4120508K	265/75R16		116S	13	31.7	10.5	7.0	620 A B	2756@44	
1602153K	225/60R17		99T	13	27.6	9.0	6.5	620 A B	1709@44	
1602154K	225/65R17	XL	106T	13	28.5	9.0	6.5	620 A B	2094@50	
4120509K	235/65R17		104S	13	29.1	9.5	7.0	620 A B	1984@44	
4120510K	245/65R17		107S	13	29.5	9.8	7.0	620 A B	2149@44	
4120511K	245/70R17		110T	13	30.6	9.8	7.0	620 A B	2337@44	
4120512K	255/65R17		110T	13	30.1	10.2	7.0	620 A B	2337@44	
4120513K	265/65R17		112S	13	30.6	10.7	8.0	620 A B	2469@44	
4120514K	265/70R17		115S	13	31.7	10.7	8.0	620 A B	2679@44	
1602155K	235/60R18	XL	107T	13	29.1	9.5	7.0	620 A B	2149@50	
4120515K	265/65R18		114T	13	31.5	10.7	8.0	620 A B	2601@44	
4120516K	265/70R18		116T	13	32.6	10.7	8.0	620 A B	2756@44	
4120517K	275/65R18		116T	13	32.1	11.0	8.0	620 A B	2756@44	
4120518K	265/50R20	XL	111T	13	30.5	10.9	8.0	620 A B	2403@50	
4120257K	275/55R20	XL	117T	13	31.9	11.2	8.0	620 A B	2833@50	
4120519K	275/60R20		115T	13	33.0	11.0	8.0	620 A B	2679@44	
1602156K	275/50R22	XL	115T	13	32.9	11.2	8.5	620 A B	2679@50	
4120526K	285/45R22	XL	114H	13	32.1	11.2	9.0	620 A B	2601@49	
4120533K	LT225/75R16	10PR	115/112S	16	29.3	8.8	6.0		2680@80	2470@80
4120534K	LT235/85R16	10PR	120/116S	16	31.7	9.3	6.0		3042@80	2778@80
4120535K	LT245/75R16	10PR	120/116S	16	30.5	9.8	7.0		3042@80	2778@80
4120536K	LT265/75R16	10PR	123/120S	16	31.7	10.5	7.0		3415@80	3085@80
1604355K	LT285/75R16	10PR	126/123S	16	32.8	11.3	8.0		3750@80	3415@80
4120537K	LT235/80R17	10PR	120/117R	16	31.8	9.3	6.0		3085@80	2835@80
4120538K	LT245/70R17	10PR	119/116S	16	30.6	9.8	7.0		3000@80	2755@80
4120539K	LT245/75R17	10PR	121/118S	16	31.5	9.8	7.0		3195@80	2910@80
4120540K	LT265/70R17	10PR	121/118S	16	31.7	10.7	8.0		3415@80	3085@80
4120541K	LT285/70R17	10PR	121/118S	16	32.8	11.5	8.0		3750@80	3415@80
4120542K	LT315/70R17	10PR	121/118S	16	34.4	12.7	9.0		3750@80	3415@80
4120543K	LT265/70R18	10PR	124/121S	16	32.6	10.7	8.0		3525@80	3195@80
4120544K	LT275/65R18	10PR	123/120R	16	32.1	11.0	8.0		3415@80	3085@80
1604601K	LT285/65R18	10PR	125/122	16	32.56	11.5	8.0		3640@80	3305@80
4120545K	LT275/70R18	10PR	125/122R	16	33.2	11.0	8.0		3640@80	3305@80
4120546K	LT265/60R20	10PR	121/118R	16	32.5	10.7	8.0		3195@80	2910@80
4120547K	LT275/55R20	10PR	120/117R	16	31.9	11.2	8.0		3085@80	2835@80
4120548K	LT275/60R20	10PR	123/120R	16	33.0	11.0	8.0		3415@80	3085@80
4120549K	LT275/65R20	10PR	126/123R	16	34.1	11.0	8.0		3750@80	3415@80
4120550K	LT285/60R20	10PR	125/122R	16	33.5	11.5	8.0		3640@80	3305@80
4120551K	LT305/55R20	10PR	121/118R	16	33.2	12.4	9.0		3195@65	2910@65
4120527K	31x10.50R15LT	6PR	109S	16	30.5	10.6	8.0		2270@50	
4120529K	33x12.50R18LT	10PR	118S	16	32.5	12.5	10.0		2910@65	
4120531K	33x12.50R20LT	10PR	114S	16	32.5	12.5	10.0		2600@65	
4120528K	35x12.50R17LT	10PR	125R	16	34.5	12.5	10.0		3640@80	
4120530K	35x12.50R18LT	10PR	123R	16	34.5	12.5	10.0		3415@65	
4120532K	35x12.50R20LT	10PR	121R	16	34.5	12.5	10.0		3195@65	

ROVELO

2 YEAR ROAD HAZARD REPLACEMENT PROGRAM

LIMITED TREADLIFE PROTECTION 45K MILE MILEAGE WARRANTY LIMITED TREADLIFE PROTECTION

RIDGETRAK R/T RT01

RUGGED TERRAIN TIRE

Meet the Ridgetrak R/T tire, expertly engineered for trucks and SUVs. Its purpose-driven design features an optimized tread pattern that guarantees stability across various terrains. A sturdy sidewall with enhanced sidewall biters increases durability and adds to its striking appearance. The RIDGETRAK R/T is built for off-road traction and smooth on-road performance.

RIDE COMFORT

Staggered lateral grooves reduce road noise, while interlocking tread blocks enhance rigidity and eliminate squirm on deep RT treads.

DESIGNED WITH PURPOSE

Step-design shoulder lugs look aggressive and provide extra protection to the shoulders and sidewalls.

OFF-ROAD CAPABLE

Aggressive sidewall biters, scalloped alternating shoulders, and stone ejectors guarantee reliable traction.

Conoce la llanta Ridgetrak R/T para camiones y SUVs. Su diseño optimizado garantiza estabilidad en cualquier terreno, con paredes laterales reforzadas para mayor durabilidad y estilo. Perfecta para tracción todoterreno y un desempeño suave en carretera.

COMODIDAD DE CONDUCCIÓN

Los surcos laterales escalonados reducen el ruido en carretera, mientras que los bloques de banda de rodadura entrelazados mejoran la rigidez y eliminan la inestabilidad en las profundas bandas RT.

DISEÑADO CON PROPÓSITO

El diseño de los peldaños de gajos de hombro tienen una apariencia agresiva y proporcionan protección adicional a los hombros y a las paredes laterales.

CAPACIDAD PARA VIAJAR FUERA DEL CAMINO

Las agresivas hendiduras de la pared lateral, los hombros alternantes festoneados y los expulsores de piedras garantizan una tracción confiable.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (1X)	Stud Size
				32/in.	in.	in.	in.		lbs@psi	lbs@psi	
1600404K	265/70R17	SL	115T	16	31.7	10.7	8	600 A B	2679@44		
1600420K	255/70R18	XL	116T	16	32.1	10.2	7	600 A B	2756@50		
1600403K	265/60R18	XL	114S	16	30.5	10.7	8	600 A B	2601@50		
1600415K	265/65R18	XL	116T	16	31.5	10.7	8	600 A B	2756@50		
1600417K	265/70R18	SL	116S	16	32.6	10.7	8	600 A B	2756@44		
1600407K	275/65R18	XL	116T	16	32.1	11.0	8	600 A B	2756@50		
1600433K	265/50R20	XL	111T	16	30.5	10.9	8	600 A B	2403@50		
5042036K	275/55R20	XL	117T	16	31.9	11.2	8	600 A B	2833@50		
1600421K	275/60R20	XL	116T	16	33.0	11.0	8	600 A B	2756@50		
1600422K	285/45R22	XL	114Q	16	32.1	11.2	9	600 A B	2601@50		
1600435K	LT245/70R17	10PR	119/116Q	18	30.6	9.8	7		3000@80	2755@80	15
1600430K	LT245/75R17	10PR	121/118Q	18	31.5	9.8	7		3195@80	2910@80	15
1600405K	LT265/70R17	10PR	123/120Q	18	31.7	10.7	8		3415@80	3085@80	15
1600412K	LT285/70R17	10PR	126/123Q	18	32.8	11.5	8		3750@80	3415@80	15
1600411K	LT265/65R18	10PR	122/119Q	18	31.5	10.7	8		3305@80	3000@80	15
1600429K	LT265/70R18	10PR	124/121Q	18	32.6	10.7	8		3525@80	3195@80	15
1600408K	LT275/65R18	10PR	123/120Q	18	32.1	11.0	8		3415@80	3085@80	15
1600432K	LT275/70R18	10PR	125/122Q	18	33.2	11.0	8		3640@80	3305@80	15
1600436K	LT275/55R20	10PR	120/117Q	18	31.9	11.2	8		3085@80	2835@80	15
1600434K	LT275/60R20	10PR	123/120Q	18	33.0	11.0	8		3415@80	3085@80	15
1600431K	LT275/65R20	10PR	126/123Q	18	34.1	11.0	8		3750@80	3415@80	15
1600428K	LT305/55R20	12PR	125/122Q	18	33.2	12.4	9		3640@80	3305@80	15
1600418K	33X12.50R17LT	10PR	120Q	18	32.5	12.5	10		3085@65		15
1600427K	35X12.50R17LT	10PR	125Q	18	34.5	12.5	10		3640@65		15
1600409K	37X12.50R17LT	8PR	124Q	18	36.5	12.5	10		3525@50		15
1600419K	33X12.50R18LT	12PR	122Q	18	32.5	12.5	10		3305@80		15
1600423K	35X12.50R18LT	12PR	128Q	18	34.5	12.5	10		3970@80		15
1600410K	37X12.50R18LT	10PR	128Q	18	36.5	12.5	10		3970@65		15
1600425K	33X12.50R20LT	12PR	119Q	18	32.5	12.5	10		3000@80		15
1600406K	35X12.50R20LT	12PR	125Q	18	34.5	12.5	10		3640@80		15
1600424K	35X13.50R20LT	12PR	126Q	18	34.5	13.6	10		3750@80		15
1600402K	37X12.50R20LT	10PR	126Q	18	36.5	12.5	10		3750@65		15
1600426K	33X12.50R22LT	12PR	114Q	18	32.5	12.5	10		2600@80		15
1600413K	35X12.50R22LT	12PR	121Q	18	34.5	12.5	10		3195@80		15
1600416K	37X12.50R22LT	12PR	127Q	18	36.5	12.5	10		3860@80		15
1600414K	37X13.50R22LT	12PR	128Q	18	36.5	13.6	10		3970@80		15

*LT tires are pinned for studs

ROVELO

2 YEAR ROAD HAZARD REPLACEMENT PROGRAM

RIDGETRAK LMD HT02

The last mile delivery industry is in constant motion and demands our tire to perform. Rovelo kept all those turns, stops and starts in mind and proudly delivers the reliable and durable Rovelo Ridgetrak LMD.

FEATURES AND BENEFITS

- Strong, robust casing engineered for commercial type tire requirements.
- Deep tread depth with advanced rubber compounds provide excellent tread wear.
- Excellent wet traction with assistance from the 4 four wide circumferential grooves.

La Industria De Entrega De Última milla Está En movimiento constante Y requiere de nuestros neumáticos para funcionar. Rovelo tiene En Cuenta todos esos giros, paros Y arranques, Y está orgulloso de proporcionarel confiable Y durable Rovelo Ridgetrak LMD.

CARACTERÍSTICAS Y BENEFICIOS

- Recauchutado fuerte y robusto, diseñado para los requisitos de los neumáticos de tipo commercial
- Banda de rodamiento profunda con compuestos avanzados de caucho que proporcionan un excelente desgaste de la banda de dodamiento
- Excelente tracción húmeda con ayuda de los 4 surcos circunferenciales amplios



Part #	Size	LI/SR	Load Range	TD	OD	SW	RW	MAX LOAD (1X)	MAX LOAD (2X)
				32/in.	in.	in.	in.	lbs@psi	lbs@psi
4120894K	195/75R16C	107/105R	D	13	27.5	7.7	5.5	2149@69	2040@69
4120895K	225/75R16C	121/120R	E	13	29.3	8.8	6.0	3197@83	3086@83
4120896K	235/65R16C	121/119R	E	13	28.0	9.5	7.0	3197@83	2998@83

Reinforced 10 ply construction increases carrying capacity over comparable LT sizes
Note : 225/75R16C LCC = 3197 lbs vs. LT225/75R16 10PR = 2680 lbs

La fabricación reforzada de 10 capas incrementa la capacidad de carga por encima de tamaños LT comparables
Nota: 225/75R16C LCC = 3197 lb vs LT225/75R16 10PR = 2680 lb

ROVELO

2 YEAR ROAD HAZARD REPLACEMENT PROGRAM

ARCTIC VISION RW01

STUDDABLE WINTER TIRE

The Rovelo Arctic Vision RW01 is a dependable studdable winter tire built for snow, ice, and extreme cold. With 3PMS (Three-Peak Mountain Snowflake) and IGS (Ice Grip Symbol) certifications, its flexible rubber and directional tread deliver confident grip and handling, clearing slush and snow with ease. From fresh powder to icy roads, it's ready for every winter drive.

ANGLED TREAD BLOCKS - 3PMS CERTIFIED

Tread blocks are strategically angled to bite into snow and ice, enhancing traction and braking performance.

WINTER GRIP - IGS CERTIFIED

RW01 incorporates high-density, multi-angle sipes that increase grip on ice and compact snow.

IMPROVED HYDROPLANING RESISTANCE

V-shaped grooves quickly evacuate water and slush, maintaining consistent contact with the road surface.

El Rovelo Arctic Vision RW01 es un neumático de invierno confiable, con opción de tachones, diseñado para nieve, hielo y frío extremo. Con certificaciones 3PMS e IGS, su compuesto flexible y banda direccional brindan agarre y control superiores, enfrentando con facilidad nieve lodosa y caminos congelados. Desde nieve fresca hasta hielo compacto, está listo para cualquier condición invernal.

BLOQUES DE BANDA EN ÁNGULO; CERTIFICACIÓN 3PMS

Bloques inclinados estratégicamente que mejoran la tracción y el frenado sobre nieve y hielo.

AGARRE EN INVIERNO; CERTIFICADO IGS

Microsurcos de alta densidad y múltiples ángulos que optimizan el agarre en hielo y nieve compacta.

RESISTENCIA AL HIDROPLANEO

Surcos en V que evacuan agua y nieve derretida, manteniendo contacto constante con la carretera.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	MAX LOAD (1X)	Stud Size
				32/in.	in.	in.	in.	lbs@psi	
1602889K	175/65R14		82T	13	23.0	7.0	5.0	1047@44	12
1602891K	175/70R14		84T	13	23.7	7.0	5.0	1102@44	12
1602894K	185/65R14		86T	13	23.5	7.4	5.5	1168@44	12
1602890K	175/65R15		84T	13	24.0	7.0	5.0	1102@44	12
1602892K	185/55R15		82T	13	23.0	7.6	6.0	1047@44	12
1602893K	185/60R15		84T	13	23.7	7.4	5.5	1102@44	12
1602895K	185/65R15	XL	92T	13	24.5	7.4	5.5	1235@50	12
1602896K	195/60R15		88T	13	24.2	7.9	6.0	1235@44	12
1602897K	195/65R15	XL	95T	13	25.0	7.9	6.0	1356@50	12
1602901K	205/65R15		94T	13	25.5	8.2	6.0	1477@44	12
1602943K	235/75R15		105S	13	28.9	9.3	6.5	2039@44	12
1603015K	205/50R16		87T	13	24.1	8.4	6.5	1201@44	12
1602899K	205/55R16	XL	94H	13	24.9	8.4	6.5	1356@50	12
1602900K	205/60R16	XL	96T	13	25.7	8.2	6.0	1389@50	12
1602902K	205/65R16	XL	95T	13	26.5	8.2	6.0	1521@44	12
1602906K	215/55R16	XL	97H	13	25.3	8.9	7.0	1609@50	12
1602908K	215/60R16	XL	95T	13	26.1	8.7	6.5	1521@44	12
1602910K	215/65R16		98T	13	27.0	8.7	6.5	1653@44	12
1602912K	215/70R16		100S	13	27.9	8.7	6.5	1764@44	12
1602921K	225/60R16		98T	13	26.6	9.0	6.5	1653@44	12
1602924K	225/65R16		100T	13	27.5	9.0	6.5	1764@44	12
1606965K	225/70R16		103S	13	28.4	9.0	6.5	1929@44	12
1606966K	235/70R16		106S	13	29.0	9.4	7.0	2094@44	12
1602898K	205/50R17	XL	93H	13	25.1	8.4	6.5	1433@50	12
1602944K	205/55R17	XL	95H	13	25.9	8.4	6.5	1521@50	12
1602903K	215/45R17	XL	91H	13	24.7	8.4	7.0	1356@50	12
1602905K	215/50R17	XL	95H	13	25.5	8.9	7.0	1521@50	12
1602888K	215/55R17	XL	98H	13	26.3	8.9	7.0	1477@50	12
1602909K	215/60R17		96T	13	27.2	8.7	6.5	1565@44	12
1602911K	215/65R17		99T	13	28.0	8.7	6.5	1709@44	12
1602914K	225/45R17	XL	94H	13	25.0	8.9	7.5	1477@50	12
1602916K	225/50R17	XL	98H	13	25.9	9.2	7.0	1653@50	12
1602918K	225/55R17	XL	101H	13	26.8	9.2	7.0	1609@50	12
1602922K	225/60R17		99T	13	27.6	9.0	6.5	1709@44	12
1602925K	225/65R17	XL	106T	13	28.5	9.0	6.5	1874@50	12
1602926K	235/45R17	XL	97T	13	25.4	9.3	8.0	1609@50	12
1602929K	235/55R17		99H	13	27.2	9.7	7.5	1709@44	12
1602933K	235/60R17		102T	13	28.1	9.5	7.0	1874@44	12
1602934K	235/65R17		104S	13	29.1	9.5	7.0	1984@44	12
1606551K	245/65R17		107T	13	29.5	9.8	7.0	2149@44	12
1602945K	265/70R17		115S	13	31.7	10.7	8.0	2679@44	12
1602904K	215/45R18	XL	93H	13	25.6	8.4	7.0	1433@50	12
1602907K	215/55R18		95T	13	27.3	8.9	7.0	1521@44	12
1602913K	225/40R18	XL	92H	13	25.1	9.1	8.0	1389@50	12
1602915K	225/45R18	XL	95T	13	25.9	8.9	7.5	1521@50	12
1602917K	225/50R18		95H	13	26.9	9.2	7.0	1521@44	12
1602919K	225/55R18		98T	13	27.8	9.2	7.0	1653@44	12
1602923K	225/60R18		100T	13	28.6	9.0	6.5	1764@44	12
1602927K	235/45R18	XL	98H	13	26.3	9.3	8.0	1477@50	12
1602928K	235/50R18	XL	101T	13	27.3	9.7	7.5	1819@50	12
1602930K	235/55R18	XL	104H	13	28.2	9.7	7.5	1764@50	12
1602942K	235/60R18		103H	13	29.1	9.5	7.0	1929@44	12
1606571K	235/65R18		106T	13	30.0	9.4	7.0	2094@44	12
1606552K	245/40R18	XL	97T	13	25.7	9.8	8.5	1609@50	12
1602935K	245/45R18	XL	100H	13	26.7	9.6	8.0	1764@50	12
1602946K	245/60R18		105T	13	29.6	9.8	7.0	2039@44	12
1602940K	255/55R18		105H	13	29.0	10.4	8.0	2039@44	12
1602947K	275/65R18		116S	13	32.1	11.0	8.0	2756@44	12
1606572K	225/40R19	XL	93T	13	26.1	9.1	8.0	1433@50	12
1602920K	225/55R19		99H	13	28.8	9.2	7.0	1709@44	12
1602948K	235/40R19	XL	96H	13	26.4	9.5	8.5	1565@50	12
1602931K	235/55R19	XL	105H	13	29.2	9.7	7.5	1819@50	12
1602936K	245/55R19	XL	107H	13	29.7	10.0	7.5	1929@50	12
1602938K	255/50R19	XL	107H	13	29.1	10.4	8.0	2149@50	12
1602932K	235/55R20	XL	105H	13	30.2	9.7	7.5	1874@50	12
1606570K	245/50R20		102T	13	29.7	10.0	7.5	1874@44	12
1602937K	255/45R20	XL	105V	13	29.1	10.0	8.5	1819@50	12
1602939K	255/50R20		105V	13	30.1	10.4	8.0	2039@44	12
1602941K	255/55R20		107H	13	31.0	10.4	8.0	2149@44	12
1606557K	265/50R20	XL	111T	13	30.5	10.9	8.5	2403@50	12
1602949K	275/55R20	XL	117T	13	31.9	11.2	8.5	2833@50	12
1602950K	275/60R20	XL	16S	13	33.0	11.0	8.0	2756@50	12
1602951K	255/40R21	XL	102V	13	29.0	10.2	9.0	1874@50	12
1602952K	265/45R21	XL	108H	13	30.4	10.5	9.0	2205@50	12
1602953K	275/45R21	XL	110H	13	30.8	10.8	9.0	2337@50	12
1606976K	275/50R22	XL	115T	13	32.9	11.2	8.5	2679@50	12
1606977K	285/45R22	XL	114T	13	32.1	11.2	9.5	2601@50	12

ROVELO

2 YEAR ROAD HAZARD REPLACEMENT PROGRAM

ARCTIC VISION LT

STUDDABLE WINTER TIRE

The Rovelo Arctic Vision LT is a studdable winter tire designed for light trucks requiring dependable traction in extreme winter conditions. Featuring a cold-weather compound and a directional tread pattern, it delivers strong grip on snow, ice, and slush. Engineered to handle heavy loads and harsh temperatures, the Arctic Vision LT offers enhanced stability and confidence for every winter job.

ICE TRACTION

High-density, multi-angle sipes create additional biting edges to enhance traction on ice and compact snow.

DURABILITY

Reinforced tread blocks and LT casing deliver added durability and stability.

WET CONTROL

V-shaped grooves channel water, slush, and wet snow from the contact patch quickly to maintain road contact and reduce hydroplaning risk.

El Rovelo Arctic Vision LT tiene capacidad de instalación de tachones diseñado para camiones ligeros que requieren tracción confiable en invierno extremo. Con un compuesto para climas fríos y un patrón de banda de rodamiento direccional, ofrece agarre fuerte en nieve, hielo y nieve lodosa. El Arctic Vision LT soporta cargas pesadas y temperaturas adversas; ofrece mayor estabilidad y confianza para el invierno.

TRACCIÓN EN EL HIELO

Los microsurcos de alta densidad y ángulo múltiple crean bordes de agarre para mejor tracción en el hielo y la nieve compactada.

DURABILIDAD

Los bloques de la banda de rodamiento reforzados y la carcasa LT ofrecen mayor durabilidad y estabilidad.

CONTROL EN CONDICIONES HÚMEDAS

Los surcos en V canalizan el agua, la nieve lodosa y la nieve húmeda desde la superficie de contacto para mantener el contacto con la carretera y reducir el riesgo de hidroplaneo.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	MAX LOAD (1X)	MAX LOAD (2X)	Stud Size
				32/in.	in.	in.	in.	lbs@psi	lbs@psi	
1606926K	235/65R16C	10PR	121/119R	13.0	28.0	9.5	7.0	3197 @83	2998 @83	15
1606920K	LT225/75R16	10PR	115/112S	17.0	29.3	8.8	6.0	2680 @80	2470 @80	15
1606922K	LT245/75R16	10PR	120/116S	17.0	30.5	9.8	7.0	3042 @80	2778 @80	15
1606928K	LT235/80R17	10PR	120/117R	17.0	31.8	9.3	6.5	3085 @80	2835 @80	15
1606930K	LT245/75R17	10PR	121/118S	17.0	31.5	9.8	7.0	3195 @80	2910 @80	15
1606948K	LT265/70R17	10PR	123/120S	17.0	31.7	10.7	8.0	3415 @80	3085 @80	15
1606932K	LT285/70R17	10PR	126/123S	17.0	32.8	11.5	8.5	3750 @80	3415 @80	15
1606942K	LT275/65R18	10PR	123/120S	17.0	32.1	11.0	8.0	3415 @80	3085 @80	15
1606944K	LT275/70R18	10PR	125/122S	17.0	33.2	11.0	8.0	3640 @80	3305 @80	15
1606946K	LT275/60R20	10PR	123/120S	17.0	33.0	11.0	8.0	3415 @80	3085 @80	15
1606924K	LT275/65R20	10PR	126/123S	17.0	34.1	11.0	8.0	3750 @80	3415 @80	15
1606934K	33×12.50R18LT	10PR	118S	17.0	32.5	12.5	10.0	2910 @65		15
1606936K	33×12.50R20LT	10PR	114S	17.0	32.5	12.5	10.0	2600 @65		15
1606938K	35×12.50R18LT	10PR	123R	17.0	34.5	12.5	10.0	3415 @65		15
1606940K	35×12.50R20LT	10PR	121R	17.0	34.5	12.5	10.0	3195 @65		15

*Factory studded option available. Ask representative for more information.

ROVELO USA LIMITED WARRANTY

All Rovelo Tire warranties must be submitted through the point of purchase.

PASSENGER & LIGHT TRUCK TIRES

This Limited Warranty / Adjustment Policy provides for tire replacement under specified conditions. This policy applies to Rovelo tires used in normal highway service (commercial applications excluded) displaying warrantable conditions. Tires that become unserviceable or wear out because of neglect or mistreatment are excluded from Rovelo warranty coverage.

THIS IS THE ONLY EXPRESSED WARRANTY MADE BY SAILUN TIRE AMERICAS NO EMPLOYEE, RETAILER, DEALER, OR REPRESENTATIVE HAS THE AUTHORITY TO MAKE ANY WARRANTY, REPRESENTATION, PROMISE OR AGREEMENT THAT IN ANY WAY VARIES THE TERMS OR CONDITIONS SET FORTH IN THIS LIMITED WARRANTY.

WARRANTY ELIGIBILITY

This warranty applies to every Rovelo replacement passenger car or light truck tire bearing the Rovelo brand name and complete Department of Transportation serial identification number while operated in normal highway use (commercial applications excluded) in the USA. These tires are covered by this warranty for the life of the original usable tread depth (the original tread depth down to the level of tread wear indicators molded at 2/32 inch) within 60 months from the date of purchase (proof of purchases required), or if proof of purchase is not available, the coverage will be 60 months from the date of manufacture. This warranty applies only to the original tire purchaser, and is not transferrable to any other party. This time period does not represent the expected service life for tires covered by this warranty.

WHAT IS NOT COVERED UNDER THIS LIMITED WARRANTY

Tires that have become unserviceable for the following reasons:

- Improper repairs or repairs that have failed. Improper repairs will void this Limited Warranty.
- Improper maintenance which can include: improper inflation or other maintenance abuses.
- Improper application or operations such as speeding, improper tire size and / or specification.
- Improper mounting / dismounting procedures, tire/wheel assembly imbalance.
- Mechanical irregularities in the vehicle or wheel, such as bent wheel assemblies, misalignment, worn or faulty components.
- Weather checking/cracking or failures after four years (48 months) from the date of manufacture.
- Accident, corrosion, vandalism, fire or damages caused by contamination by petroleum or other chemical products.
- Tires used in commercial applications such as taxis, shuttle vehicles and couriers.
- Irregular tread wear, or worn-out (beyond 2/32nds remaining tread depth) is not covered under the Rovelo Limited Warranty.
- Road hazard injuries or damages caused by obstacles or debris, such as cuts, punctures (whether repairable or not), snags, bruises, tears, abrasions or impact breaks (whether repairable or not), etc.
- Damage from racing, off road use (forestry roads, gravel, rock) and misapplication of the tire to vehicle.

ADDITIONAL EXCLUSIONS

- Materials added such as fillers, sealants, balancing substances and external tire treatments. If the added material is the cause of a failure the warranty will be deemed as void.
- Tires submitted for ride disturbance complaints after 25% (2/32") tread wear.
- Tires on vehicles registered or operated outside of the USA.
- Tires not purchased in the USA through the Sailun Tire Americas distribution channel.
- Tires purchased as used.
- Tires branded by Rovelo to note special classification at time of purchase, such as "NA" (non-adjustable), or tires altered by notching or buffing.
- Tires used on vehicles in racing or special applications.
- Tires rendered unserviceable due to snow chains or studs.
- Flat spotting due to improper storage or caused by brake lock.

NOTE: Consequential damage mentioned above may not apply to you based on individual State limitations.

WHAT IS WARRANTED

Tires that have become unserviceable for reasons other than stated above, within 48 months of the date of manufacturer or 60 months from the date of purchase (proof of purchase required) during its useable tread life, the tires will be replaced in accordance with this warranty.

LIMITED MILEAGE WARRANTY

Model	Defects/ Materials	# Months	Miles/ Months
INSTINCT AS01	✔	60	60K/60
INSTINCT AW	✔	60	60K/60
INSTINCT SUV	✔	60	60K/60
INSTINCT UHP AS HP01	✔	60	50K/60
RIDGETRAK H/T HT02 - LT Tires	✔	60	50K/60
RIDGETRAK H/T HT02 - P - Metric Tires	✔	60	60K/60
RIDGETRAK A/T II	✔	60	50K/60*
RIDGETRAK R/T RT01	✔	60	45K/60*
RIDGETRAK LMD HT02	✔	60	-
ARCTIC VISION RW01	✔	60	-
ARCTIC VISION LT	✔	60	-

NOTE: All tire models, staggered vehicle fitments have half mileage for rear tires if different size than the front tires.

All tire models, half mileage warranty applies when used on EV and PHEV vehicles.

Select Rovelo tires are assigned a Limited Mileage Warranty that protects the consumer against premature tread wear. If a tire reaches the end of its "usable tread life" before the stated mileage protection, the consumer will be issued a replacement Rovelo tire on a prorated basis, which means the consumer will be responsible for a percentage of the replacement cost. In order to maintain limited mileage protection, all tires must be properly inflated, balanced, rotated and aligned as recommended by vehicle manufacturer. All claims must be accompanied by the original purchase invoice as well as invoices for all on time services provided. Under all circumstances, the cost of mounting, balancing and any other service charges including applicable taxes, disposal fees are required to be paid by the consumer.

APPROVED TIRE ROTATION INTERVALS AND PATTERNS

The purpose of regularly rotating tires is to prolong their useful life by achieving more uniform wear for all tires on a vehicle. Before rotating tires, always consult the owner's manual for rotation recommendations for specific vehicles. If no rotation period is specified, tires should be rotated, at minimum, every 6,000 miles or at any sign of uneven wear. The first rotation is the most important. Rotating the tires as recommended by the vehicle or tire manufacturer will help even out the amount of wear on each tire and extend the life of the entire set. Such tires include: "Temporary Use Spares", unidirectional tires and tires with asymmetric tread designs. Also, some vehicles may have different sized tires mounted on the front and rear axles, and these different sized tires have rotation restrictions. Check the owner's manual for the proper rotation recommendations for these special cases. When tires are rotated, the inflation pressures must be adjusted for the tires' new positions in accordance with the actual loads on that wheel position and the vehicle manufacturer's recommendations. Underinflated or overinflated tires may result in poor handling, uneven tread wear, and increased fuel consumption. If the tires show uneven wear, ask the service person to check for and correct any misalignment, imbalance, or other mechanical problem before rotation.

ADJUSTMENT POLICY

Passenger and Light Truck Tires When the original usable tread is worn 25% (2/32 or less, and a warrantable condition is found, the tire will be replaced with a comparable new Rovelo tire free of charge. Replacement tires will be mounted and balanced at the vehicle owner's expense. Other service charges such as tire rotation, alignment or applicable taxes are payable by the customer. When a tire has worn past the above specified period for free replacement and a warrantable condition is found, the customer must pay for the cost of a new comparable Rovelo passenger or light truck tire on a prorated basis. The dealer shall determine this cost by multiplying the percentage of usable tread worn by the current retail selling price (Suggested Retail Price x 80%) of that tire at the time of warranty replacement. The cost of mounting, balancing and any other service charges or applicable taxes are payable by the customer.

ROVELO

+ ROAD HAZARD REPLACEMENT PROGRAM

Rovelo Tire offers a “limited, free replacement” road hazard program which applies to all Rovelo passenger and light truck patterns. This program is a gesture of goodwill and not a program that your tire will not fail due to a road hazard. This free replacement road hazard program applies only during the first 3/32 of the original usable tread or two years from the date of purchase, whichever comes first. Rovelo will replace the un-repairable tire with a similar new Rovelo Tire. Mounting, balancing and applicable taxes are the responsibility of the consumer. Once a tire is worn beyond the first 3/32, or more than two years from date of purchase, this road hazard program is null and void. Repairable tires must always be repaired at the vehicle owner’s expense.

The Road Hazard Replacement Program applies to all tires purchased after January 1, 2025. (Tires purchased prior to 1/1/2025 do not qualify for this program)



+ NOTES | NOTER

ROVELO



+ ROVELOTIREUSA.COM

+ **Address:** 9610 Ooltewah Industrial Rd
Ooltewah, TN 37363, USA
+ **Head Office:** (289) 499-3240
+ **Toll-free at:** 1-855-499-3240